

KOTTUCHERRY COMMUNE PANCHAYAT
SCHEDULE OF QUANTITIES

Name of work : Construction of Recreation Centre at Jeeva Nagar in Kottucherry Commune.

| Sl. No | Sub heads and item of work | Quantity | Per | Rate | | Amount |
|--------|---|-----------|--------------------------|--------|-------|--------|
| | | | | Figure | Words | |
| 1 | Earth work in excavation by mechanical means (Hydraulic excavator)/manual means in foundation trenches or drains (not exceeding 1.5m in width or 10 sqm on plan) including dressing of sides and ramming of bottoms, lift upto 1.5m, including getting out the excavated soil and disposal of surplus excavated soil as directed , within a lead of 50m -All kinds of soil. | 29.00 Cum | 1 Cum (One Cubic Metre) | | | |
| 2 | Filling available excavated earth (excluding rock) in trenches, Plinth, sides of foundation etc., in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering lead upto 50m and lift upto 1.5m. | 29.00 Cum | 1 Cum (One Cubic Metre) | | | |
| 3 | Supplying and filling with good earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth consolidating each deposited layers by ramming and watering etc. complete including all lead and lift. | 25.00 Cum | 1 Cum (One Cubic Metre) | | | |
| 4 | Supplying and filling in plinth with river sand under floors including, watering, ramming consolidating and dressing complete. | 8.00 Cum | 1 Cum (One Cubic Metre) | | | |
| 5 | Providing and laying in position cement concrete of specified grade excluding the cost of centring and shuttering all works upto plinth level 1:5:10 (1 cement : 5 sand : 10 graded stone aggregate 40mm nominal size) | 9.00 Cum | 1 Cum (One Cubic Metre) | | | |
| 6 | Brick work with modular bricks of class designation 35 in foundation and plinth in cement mortar 1:6 (1 cement: 6 coarse sand) | 7.00 Cum | 1 Cum (One Cubic Metre) | | | |
| 7 | Brick work with modular bricks of class designation 35 in foundation and plinth in cement mortar 1:4 (1 cement: 4 coarse sand) | 0.50 Cum | 1 Cum (One Cubic Metre) | | | |
| 8 | Brick work with table moulded bricks of class designation 35 in superstructure above plinth level upto floor V level in all shapes and sizes in cement mortar 1:6 (1 cement : 6 coarse sand) | 27.00 Cum | 1 Cum (One Cubic Metre) | | | |
| 9 | Providing precast cement concrete jali 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 6mm nominal size) reinforced with 1.6mm dia mild steel wire including centering and shuttering, roughening, cleaning, fixing and finishing in cement mortar 1:3 (1cement : 3 sand) etc. complete excluding plastering of the jambs, sills and soffits - 40mm. | 1.00 Sqm | 1 Sqm (One Square Metre) | | | |
| 10 | Providing and laying in position cement concrete of specified grade excluding the cost of centring, shuttering, finishing & reinforcement all works upto plinth level 1:1.5:3 (1 cement : 1.5 sand : 3 graded stone aggregate 20mm nominal size) | 8.00 Cum | 1 Cum (One Cubic Metre) | | | |

| Sl. No | Sub heads and item of work | Quantity | Per | Rate | | Amount |
|--------|---|-------------|--------------------------|--------|-------|--------|
| | | | | Figure | Words | |
| 11 | Reinforced cement concrete work in walls (any thickness) including attached pilasters, buttresses, plinth and string course, fillets, columns pillars, piers, abutments, posts and struts, etc., upto floor five level excluding cost of centring shuttering, finishing and reinforcement 1:1.5:3 (1 cement : 1.5 sand : 3 graded stone aggregate 20mm nominal size) | 2.00 Cum | 1 Cum (One Cubic Metre) | | | |
| 12 | Reinforcement cement concrete work in beams, suspended floors, roofs having slope upto 15 degree landings, balconies, shelves, chajjahs, lintels, bands, plain window sills, staircases and spiral staircases upto floor five level excluding cost of centring, shuttering, finishing and reinforcement with 1:1.5:3 (1 cement : 1.5 sand : 3 graded stone aggregate 20mm nominal size) | 15.00 Cum | 1 Cum (One Cubic Metre) | | | |
| 13 | Centring and shuttering including strutting, propping etc.and removal of form for:Foundations , footings, bases of columns, etc. for mass concrete.- Using steel sheet with M.S.frames | 8.00 Sqm | 1 Sqm (One Square Metre) | | | |
| 14 | Centring and shuttering including strutting, propping etc. and removal of form for: lintels, beams, plinth beams, girders, bressumers and cantilevers.- Using steel sheet with M.S.frames. | 91.00 Sqm | 1 Sqm (One Square Metre) | | | |
| 15 | Centring and shuttering including strutting, propping etc. and removal of form for : suspended floors, roofs, landings, balconies and access platform - Using steel sheet with M.S.frames | 95.00 Sqm | 1 Sqm (One Square Metre) | | | |
| 16 | Centring and shuttering including strutting, propping etc. and removal of form for: columns, pillars, piers, abutments, posts and struts.- Using steel sheet with M.S.frames | 23.00 Sqm | 1 Sqm (One Square Metre) | | | |
| 17 | Centring and shuttering including strutting, propping etc. and removal of form for: Stairs (excluding landings) except spiral - staircases - with water proof ply 12mm thick , mango / silver wood scantling and casurina poles | 6.00 Sqm | 1 Sqm (One Square Metre) | | | |
| 18 | Half brick masonry with FPS bricks of class designation 35 in superstructure above plinth level upto floor V level in cement mortar 1:3 (1 cement: 3 coarse sand) | 9.30 Sqm | 1 Sqm (One Square Metre) | | | |
| 19 | Reinforcement for R.C.C work including straightening , cutting, bending , placing in position and binding all complete - Thermo - Mechanically Treated Bars(ISI BRAND OF APPROVED MAKE) including placing the M30 grade Athees make cover block @ 60cm centre to centre. | 3000.00 Kgs | 1 Kg (One Kilogram) | | | |
| 20 | Providing wood work in frames of doors, windows, clerestory windows and other frames, wrought framed and fixed in position - Padak wood. | 0.50 Cum | 1 Cum (One Cubic Metre) | | | |

| Sl. No | Sub heads and item of work | Quantity | Per | Rate | | Amount |
|--------|---|------------|--------------------------|--------|-------|--------|
| | | | | Figure | Words | |
| 21 | Providing and fixing panelled or panelled and glazed shutters for doors , windows and clerestory windows including ISI marked black enamelled M.S butt hinges with necessary screws excluding panelling which will be paid for separately. - Padak wood teak wood - 35mm thick shutters. | 7.00 Sqm | 1 Sqm (One Square Metre) | | | |
| 22 | Providing and fixing panelled or panelled and glazed shutters for doors, windows and clerestory windows including ISI marked black enamelled M.S. butt hinges with necessary screws excluding, panelling which will be paid for separately - Padak wood 30 mm thick shutters | 13.00 Sqm | 1 Sqm (One Square Metre) | | | |
| 23 | Providing and fixing panelling or panelling and glazing in panelled or panelled and glazed shutters for doors, windows and clerestory windows (area of opening for panel inserts excluding portion inside grooves or rebates to be measured). Panelling for panelled or panelled and glazed shutters 25mm to 40mm thick: Padak wood | 13.00 Sqm | 1 Sqm (One Square Metre) | | | |
| 24 | Providing and fixing M.S. grills of required pattern in frames of windows etc. with M.S. flats, square or round bars etc. all complete - fixed to openings / wooden frames with rawl plugs, screws etc.. | 366.00 Kgs | 1 Kg (One Kilogram) | | | |
| 25 | Providing 40 x 5mm flat iron hold fast 40cm long including fixing to frame with 10mm diameter bolts nuts and wooden plugs and embedding in cement concrete block 30 x 10 x 15cm 1:3:6 (1 cement : three sand : six graded stone aggregates 20mm nominal size) | 50.00 Nos. | 1 No.(One Number) | | | |
| 26 | Providing and fixing ISI marked M.S. pressed butt hinges bright finished with necessary screws etc. complete - 125x65x2.12mm. | 12.00 Nos. | 1 No.(One Number) | | | |
| 27 | Providing and fixing aluminium sliding door bolts ISI marked anodised (anodic coating not less than grade AC 10 as per IS 1868) transparent or dyed to required colour or shade with nuts and screws etc., complete - 300 x 16mm. | 5.00 Nos. | 1 No.(One Number) | | | |
| 28 | Providing and fixing aluminium tower bolts ISI marked anodised (anodic coating not less than grade AC 10 as per IS 1868) transparent or dyed to required colour or shade with necessary screws etc., complete 250 x 10mm | 9.00 Nos. | 1 No.(One Number) | | | |
| 29 | Providing and fixing aluminium tower bolts ISI marked anodised (anodic coating not less than grade AC 10 as per IS 1868) transparent or dyed to required colour or shade with necessary screw etc., complete 150 x 10mm. | 47.00 Nos. | 1 No.(One Number) | | | |
| 30 | Providing and fixing aluminium handles ISI marked anodised (anodic coating not less than grade AC 10 as per IS 1868) transparent or dyed to required colour or shade with necessary screws etc., complete 125mm | 6.00 Nos. | 1 No.(One Number) | | | |

| Sl. No | Sub heads and item of work | Quantity | Per | Rate | | Amount |
|--------|---|-----------|---------------------------|--------|-------|--------|
| | | | | Figure | Words | |
| 31 | Providing and fixing M.S fan clamp type - I of 16mm dia MS bar bend to shape with hooked ends in RCC slabs beams during laying including painting the exposed portion of loop all as per standard design complete. | 6.00 Nos | 1 No.(One Number) | | | |
| 32 | Providing and laying ceramic glazed floor tiles 300x300 mm (thickness to be specified by the manufacturer) of first quality conforming to IS: 15622 of approved make (Bell / Johnson / Regency / Somany / Naveen / Asian) in all colors, shades, except white, ivory, grey, fume red brown laid on 20mm thick bed of cement mortar 1:4 (1 cement : 4 coarse sand) including pointing the joints with white cement and matching pigments etc., complete. | 63.00 Sqm | 1 Sqm (One Square Metre) | | | |
| 33 | Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS : 15622 (thickness to be specified by the manufacture of approved make (Jhonson / Asian / Somany / Nitco) in all colours, shades of size 200 x 300 mm as approved by Engineer -in-charge in skirting, risers of steps and dados over 12mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm. Including pointing in white cement mixed with pigment of matching shade complete. - size 200 x 300mm | 4.00 Sqm | 1 Sqm (One Square Metre) | | | |
| 34 | Painting top of roofs with bitumen of approved quality at 17Kg/10Sqm impregnated with a coat of coarse sand at 60cudm/10sqm including cleaning the slab surface with brushed and finally with a piece of cloth lightly soaked with kerosene oil complete - with residual type petroleum bitumen of penetration 80/100. | 53.00 Sqm | 1 Sqm (One Square Metre) | | | |
| 35 | Lime concrete terracing on roofs of required thickness laid fall with 25mm nominal size brick aggregate and 50% lime mortar 1:2 (1 lime putty : 2 surkhi) rammed and finished with gur and belgiri treatment complete including rounding of junctions with parapet wall complete. | 6.00 Cum | 1 Cum (One Cubic Metre) | | | |
| 36 | Providing and laying pressed clay tiles (as per approved pattern 20mm nominal thickness and of approved size) on roofs jointed with cement mortar 1:4 (1 cement : 4 coarse sand) mixed with 2% integral water proffing compound laid over a bed of 20mm cement mortar 1:4 (1 cement : 4 coarse sand) and finished neat complete. | 56.00 Sqm | 1 Sqm (One Square Metre) | | | |
| 37 | Providing and fixing on wall face unplasticised rigid PVC rain water pipes conforming to IS : 13592 type A including jointing with seal ring conforming to IS : 5382 leaving 10mm gap for thermal expansion, (i) single socketed pipes. 110mm diameter. | 12.00 Rmt | 1 Rmt (One Running Metre) | | | |
| 38 | Providing and fixing on wall face or column face unplasticised PVC moulded fittings or accessories for unplasticised PVC rain water pipes conforming to IS 13592 type 'A' including jointing with seal ring conforming to IS 5382 leaving 10mm gap for thermal expansion - bend 87.5 degree 110mm bend. | 6.00 Nos. | 1 No.(One Number) | | | |

| Sl. No | Sub heads and item of work | Quantity | Per | Rate | | Amount |
|--------|--|------------|---------------------------|--------|-------|--------|
| | | | | Figure | Words | |
| 39 | Providing and fixing on wall face or column face unplasticised PVC moulded fittings or accessories for unplasticised rigid PVC rain water pipes conforming to IS 13592 including jointing with seal ring conforming to IS 5382 leaving 10mm gap for thermal expansion - shoe (plain) 110mm shoe. | 4.00 Nos. | 1 No.(One Number) | | | |
| 40 | Providing and fixing unplasticised-PVC pipe clips of approved design to unplasticised - PVC rain water pipes by means of 50x50x50mm hard wood plugs, screwed with M.S. screws of required length including cutting brick work and fixing in cement mortar 1:4 (1 cement : 4 sand) and making good the walls etc. complete.- 110mm | 16.00 Nos. | 1 No.(One Number) | | | |
| 41 | 12mm cement plaster of mix 1:4 (1 cement : 4 fine sand) | 9.00 Sqm | 1 Sqm (One Square Metre) | | | |
| 42 | 15mm cement plaster on the rough side of single or half brick wall of mix cement mortar 1:6 (1 cement : 6 fine sand) | 121.00 Sqm | 1 Sqm (One Square Metre) | | | |
| 43 | 12mm cement plaster of mix 1:6 (1 cement : 6 coarse sand) | 160.00 Sqm | 1 Sqm (One Square Metre) | | | |
| 44 | 6mm cement plaster to ceiling mix 1:3 (1 cement : 3 fine sand) . | 66.00 Sqm | 1 Sqm (One Square Metre) | | | |
| 45 | Finishing walls with water proofing cement of required shade - new work (two or more coats) applied @ 3.84 Kg/10m ² . | 281.00 Sqm | 1 Sqm (One Square Metre) | | | |
| 46 | White washing with lime to give an even shade new work (three or more coats) | 66.00 Sqm | 1 Sqm (One Square Metre) | | | |
| 47 | Painting with synthetic enamel paint of approved brand and manufacture in all shades to give an even shade - new steel work (two or more coats) on new work. | 33.00 Sqm | 1 Sqm (One Square Metre) | | | |
| 48 | Providing and fixing white vitreous china water closet squatting pan (Indian type) Orissa pattern W.C pan of size 580 x 440mm. | 1.00 No. | 1 No.(One Number) | | | |
| 49 | Providing and fixing white vitreous china wash basin including making all connections but excluding the cost of fittings flat back wash basin of size 450 x 300 mm. | 1.00 No. | 1 No.(One Number) | | | |
| 50 | Providing and fixing PVC waste pipe for sink or wash basin including PVC waste fittings complete - Semi rigid pipe - 32mm dia. | 1.00 No. | 1 No.(One Number) | | | |
| 51 | Providing and fixing G.I pipes complete with GI fittings and clamps including cutting and making good the walls etc., internal work exposed in wall 20mm dia nominal bore (1.58 per/Kg/m) | 28.00 Rmt | 1 Rmt (One Running Metre) | | | |

| Sl. No | Sub heads and item of work | Quantity | Per | Rate | | Amount |
|--------|--|-------------|---------------------------|--------|-------|--------|
| | | | | Figure | Words | |
| 52 | Providing and fixing G.I pipes complete with GI fittings and clamps including cutting and making good the walls etc., internal work exposed in wall 32mm dia nominal bore | 16.00 Rmt | 1 Rmt (One Running Metre) | | | |
| 53 | Providing and fixing brass bib cock of approved quality - 15mm nominal bore. | 3.00 Nos. | 1 No.(One Number) | | | |
| 54 | Providing and fixing brass gate valve with C.I wheel of approved quality (screwed end) - 20mm nominal bore. | 1.00 No. | 1 No.(One Number) | | | |
| 55 | Providing and placing on terrace (at all floor levels) polyethylene water storage tank of ISI 12701 marked with cover and suitable locking arrangement and making necessary holes for inlet, outlet and over flow pipes with all fittings but without the base support for tank. | 500.00 Lts | 1 Lt. (One Litre) | | | |
| 56 | Supplying fixing and commissioning of Suguna/ Texmo /Sharp 1 HP monoblock pumpset slow speed single phase motor. The rate include the cost of pumpset , pumpset fixing in position and test run etc. complete as directed by the Engineer-in-charge. | 1.00 No. | 1 No.(One Number) | | | |
| 57 | Demolishing brick work manually / mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead;-in cement mortar. | 16.00 Cum | 1 Cum (One Cubic Metre) | | | |
| 58 | Demolishing cement concrete manually / mechanical means including disposal of material within 50 metres lead; - 1:4:8 or leaner mix. | 3.00 Cum | 1 Cum (One Cubic Metre) | | | |
| 59 | Dismantling tiled roofing with battens boarding etc. complete including stacking of serviceable material and disposal of unserviceable material within 50 metres lead. | 27.00 Sqm | 1 Sqm (One Square Metre) | | | |
| 60 | Taking out doors, windows and clerestory window shutters (steel or wood) including stacking within 50 metres lead-of area 3 sqm. and below | 3.00 Nos. | 1 No.(One Number) | | | |
| 61 | Supplying and fixing of following size of PVC conduit alongwith the accessories in surface/recess Conduit including cutting the wall and making good the same in case of recessed conduit as required. Make: Avonplast /Vijaya:- 25mm dia | 96.00 Mts. | 1 Mt. (One Metre) | | | |
| 62 | Supplying and fixing of following size of PVC conduit alongwith the accessories in surface/recess Conduit including cutting the wall and making good the same in case of recessed conduit as required. Make: Avonplast/Vijaya:- 32mm dia | 10.00 Mts. | 1 Mt. (One Metre) | | | |
| 63 | Supplying and laying of following size of PVC conduit in roof slab alongwith the accessories. Make: Avonplast/Vijaya:- 25mm dia | 72.00 Mts. | 1 Mt. (One Metre) | | | |
| 64 | Supplying and drawing of 1.5 sqmm. FR PVC insulated, copper conductor, single core cable in the existing surface / recessed, PVC/steel conduit/PVC casing and capping as required.Make: Finolex/ Polycab:- | 240.00 Mts. | 1 Mt. (One Metre) | | | |

| Sl. No | Sub heads and item of work | Quantity | Per | Rate | | Amount |
|--------|---|------------|---------------------|--------|-------|--------|
| | | | | Figure | Words | |
| 65 | Supplying and drawing of 2.5 sqmm. FR PVC insulated, copper conductor, single core cable in the existing surface / recessed, PVC/steel conduit/PVC casing and capping as required.Make: Finolex/ Polycab:- | 10.00 Mts. | 1 Metre (One Metre) | | | |
| 66 | Supplying and fixing of following size of PVC deep junction box in required position along the line of PVC conduit as required .Make:Avonplast/Vijaya:- 25mm deep Junction Box one way. | 5.00 Nos. | 1 No.(One Number) | | | |
| 67 | Supplying and fixing of following size of PVC deep junction box in required position along the line of PVC conduit as required .Make:Avonplast/Vijaya:- 25mm deep Junction Box two way. | 5.00 Nos. | 1 No.(One Number) | | | |
| 68 | Supplying and fixing of following size of PVC deep junction box in required position along the line of PVC conduit as required .Make:Avonplast/Vijaya:- 25mm deep Junction Box three way. | 4.00 Nos. | 1 No.(One Number) | | | |
| 69 | Supplying and fixing of following size of PVC deep junction box in required position along the line of PVC conduit as required .Make:Avonplast/Vijaya:- 25mm deep Junction Box four way. | 4.00 Nos. | 1 No.(One Number) | | | |
| 70 | Supplying and fixing of following size of PVC junction box in required position along the line of PVC conduit as required.Make:Avonplast/Vijaya:- 25mm Junction Box one way | 14.00 Nos. | 1 No.(One Number) | | | |
| 71 | Supplying and fixing of following size of PVC junction box in required position along the line of PVC conduit as required.Make:Avonplast/Vijaya:- 25mm Junction Box two way | 4.00 Nos. | 1 No.(One Number) | | | |
| 72 | Supplying and fixing of following size of PVC junction box in required position along the line of PVC conduit as required.Make:Avonplast/Vijaya:- 25mm Junction Box three way | 4.00 Nos. | 1 No.(One Number) | | | |
| 73 | Supplying and fixing of following size of PVC junction box in required position along the line of PVC conduit as required.Make:Avonplast/Vijaya:- 25mm Junction Box four way | 4.00 Nos. | 1 No.(One Number) | | | |
| 74 | Supplying and fixing of following size of steel conduit alongwith accessories in surface/recess including painting in case of surface conduit or cutting the wall and making good the same in case of recessed, conduit as required :- 32mm | 5.00 Mts. | 1 Metre (One Metre) | | | |
| 75 | Supplying and fixing of the following sizes of Teak wooden board on recess including cutting the wall and finishing the surface good the same as required - 375mm X 300mm X 50mm. Deep | 2.00 Nos. | 1 No.(One Number) | | | |
| 76 | Supplying and fixing of the following sizes of Teak wooden board on recess including cutting the wall and finishing the surface good the same as required - 150mm X 150mm X 50mm. Deep | 1.00 No. | 1 No.(One Number) | | | |

| Sl. No | Sub heads and item of work | Quantity | Per | Rate | | Amount |
|--------|--|------------|---------------------|--------|-------|--------|
| | | | | Figure | Words | |
| 77 | Providing and fixing of following size phenolic coated sheet on existing wooden board: - 375mm X 300mm X 3mm Thick | 2.00 Nos. | 1 No.(One Number) | | | |
| 78 | Providing and fixing of following size phenolic coated sheet on existing wooden board: - 150mm X 150mm X 3mm Thick | 1.00 No. | 1 No.(One Number) | | | |
| 79 | Supplying and fixing S.P 1 way 5/6amps piano / flush type switch on the existing switch box/cover including connections etc. as required.Make: Kundan / Anchor / Vinay :- | 26.00 Nos. | 1 No.(One Number) | | | |
| 80 | Supplying and fixing 3 pin 5/6amps piano/flush type socket outlet on the existing switch box/cover including connections etc. as required.Make: Kundan / Anchor / Vinay:- | 2.00 Nos. | 1 No.(One Number) | | | |
| 81 | Supplying and fixing 5/6amps indicator on the existing switch box/cover including connections etc. as required. Make: Kundan/Anchor/Vinay:- | 3.00 Nos. | 1 No.(One Number) | | | |
| 82 | Supplying and fixing 10 amps Kit Kat Fuse on the existing switch box/cover including connections etc. as required. Make: Kundan/Anchor/Vinay:- | 3.00 Nos. | 1 No.(One Number) | | | |
| 83 | Supplying and fixing jumbo type Batten/Angle Holder including connections etc. as required .Make: Kundan/Anchor/Vinay:- | 4.00 Nos. | 1 No.(One Number) | | | |
| 84 | Supplying and fixing 3 plate, 5 amp.ceiling rose on the existing junction box/wooden block including connections etc. as required.Make: Kundan/Anchor/Vinay:- | 24.00 Nos. | 1 No.(One Number) | | | |
| 85 | Installation, testing and commissioning of prewired, all kind of surface mount light fittings, complete with all accessories etc.directly on high ceiling/wall, including connections with 16/0.20mm twin core FR PVC sheathed flat flexible, copper cable etc. as required. | 15.00 Nos. | 1 No.(One Number) | | | |
| 86 | Installation, testing and commissioning of ceiling fan / wall mounting fan and wiring the down rod of standard length (upto 30cm) with 14/0.86mm plastic insulated twisted copper wire including earth as required. | 4.00 Nos. | 1 No.(One Number) | | | |
| 87 | Earthing with G.I.medium pipe 3.0 mt long and 40mm dia including accessories 250 x 50 x 6 mm G.I clamp with 12mm bolt, nut and washer for connecting earth wire, RCC ring enclosure and cover plate complete as required:- | 1.00 No. | 1 No.(One Number) | | | |
| 88 | Service connection from electricity department supply post to department metre single phase line including labour charges 3/20 PVC insulated copper wire 7/10 G.I. wire parcel in reel etc., as required. | 90.00 Mts. | 1 Metre (One Metre) | | | |

| Sl. No | Sub heads and item of work | Quantity | Per | Rate | | Amount |
|--------|---|-------------|---------------------|--------|-------|--------|
| | | | | Figure | Words | |
| 89 | 1400mm sweep double ball bearing ceiling fan Make : Almonard/Usha. | 7.00 Nos. | 1 No.(One Number) | | | |
| 90 | 1 x 40W box type single tube light fitting with copper choke & starter without tube. Make: Philips / Bajaj. 40W tube light Make : Philips. | 10.00 Nos. | 1 No.(One Number) | | | |
| 91 | Bulk head fitting aluminium alloy body heat resistant prismatic glass cover with specially designed gasket GLS 100W type). Make : Philips / Bajaj. | 4.00 Nos. | 1 No.(One Number) | | | |
| 92 | 32A cutout fuse unit Make: Kundan. | 1.00 No. | 1 No.(One Number) | | | |
| 93 | Dismantling wood work in frame trusses purlin and rafter upto 10m span and 5m height including stacking the material within 50m lead of sectional area below 40sqm. | 156.00 Mts. | 1 Metre (One Metre) | | | |